

Claims:

~~Added 12/18~~
~~Sub 12, 17~~

5 1. Apparatus for transporting workpieces in a press, press line, multi-stage press for large components or the like, each processing station (6.1 - 6.n) having an independent transporting apparatus (2.1 - 2.n) which transports the workpiece and is intended for executing a biaxial transporting movement, characterized in that the transporting apparatus (2.1 - 2.n) comprises a
10 drive system which is intended for a crossmember (25) provided with workpiece-retaining means and which has stationary drives, in particular drive motors (A1, A2, 16, 17, 39, 40), which each act on movement-transmission means (8 - 13, 16 - 24, 41 - 49),
15 a regulation of the direction of rotation and of the rotational speed and/or standstill of the drives, in particular drive motors, bringing about a co-ordinated movement of the movement-transmission means such that any desired programmable traveling curve of the
20 crossmember (25) is possible.

2. Apparatus according to Claim 1, characterized in that the crossmember (25) is mounted on a slide (36, 53) with linear guide (29, 37, 56, 57).

A

25 3. Apparatus according to Claims 1 ^{or} ~~and~~ 2, characterized in that the movement-transmission means (8 - 13, 16 - 24, 41 - 48) is designed as a rack drive for executing a longitudinal movement and/or a lifting and/or lowering movement of a slide (36, 53) for the
30 crossmember (25).

~~SUB 17~~

35 4. Apparatus according to one of the preceding claims, characterized in that a longitudinal movement and/or a lifting and/or lowering movement of the bearing slide (36, 53) for the crossmember (25) takes place by means of two parallel racks (19, 21, 42, 44) which can be driven, via gearwheels (18, 20, 41, 43),

SUB A1
by stationary drives, in particular drive motors (16, 17, 39, 40).

5. Apparatus according to one of the preceding
5 claims, characterized in that the 2 parallel racks (19, 21) are arranged horizontally.

6. Apparatus according to one of the preceding
10 claims, characterized in that the 2 parallel racks (42, 44) are arranged vertically.

7. Apparatus according to one of the preceding
claims, characterized in that two parallel racks (19, 21, 42, 44) or the like act jointly on drive gears (22, 23, 45) such that it is possible to set a lifting
15 and/or lowering movement of a carrying slide (36, 51, 53).

8. Apparatus according to one of the preceding
20 claims, characterized in that the gearwheels (22, 23, 45, 46) connected to one another via a common shaft (38, 47) are mounted in the slide (36, 51), and in that the gearwheel (22, 45) is fastened at one end of the shaft (38, 47) and gearwheel (23, 46) is fastened at
25 the other end of the shaft (38, 47).

9. Apparatus according to one of the preceding
claims, characterized in that the crossmember (25) is
arranged pivotably and the drive (26) for the pivoting
30 movement is fastened on the slide (36, 53).

10. Apparatus according to Claim 1, characterized in
that an adjusting and lifting apparatus (4) is provided
for a lifting and/or lowering movement of the
35 transporting system (2) or component systems
(2.1 - 2.n).

SUB A2
11. Apparatus according to one of the preceding
claims, characterized in that the rack-gearwheel drive

12. Apparatus according to one of the preceding claims, characterized in that movement-transmission means (49) is a toothed belt (49) with deflecting rollers (50), and the toothed belt (49) is firmly connected to vertical slide (51) via a fixed point (52) and to horizontal slide (53) via a fixed point (54).
13. Apparatus according to Claim 1, characterized in that movement-transmission means (8 - 11, 18 - 22) run horizontally in the transporting direction and, transversely to the transporting apparatus, are offset in each case in relation to following movement-transmission means (18.1 - 22.1).